



### Keypoints:

- Conform Intel ATX 12v ver 2.3 and EPS 12v
- High Efficiency (80Plus bronze certification)
- Cable length at least 45 cm
- Silent 12cm fan (automatic speed control)
- Active PFC (Power factor correction)
- OCP / OVP / SCP Protections

### Specifications:

Description	
Article number	RC-ProE-A600
Packaging unit (per carton)	6 Pieces
Net weight per piece	1,90 Kg
Gross weight per piece	2,11 Kg
Gross weight per carton	14,8 Kg
Net dimensions per piece (W x H x D)	14 x 15 x 8,6cm
Gross dimensions per piece (W x H x D)	24 x 11 x 22cm
Gross dimensions per carton (W x H x D)	32 x 26 x 45 cm
Color	Black coated shell
On-Off power switch	Yes
Accessories	2 Pcs. Cable ties 4 Pcs. Black screws AC Powercable (CE)

### Connectors:

Description	
M/B 20+4Pins	1 Pc.
M/B 4+4 Pins ATX	1 Pc.
Pci-E 6+2 Pins	1 Pc.
Pci-E 6 Pins	1 Pc.
SATA 15 Pins	6 Pcs.
MOLEX 4 Pins	4 Pcs.
FDD 4 Pins	1 Pc.

### Delivered cables:

	Connection	Connector 1	Connector 2	Connector 3	Amount
Mainboard atx	Onboard	45cm 20+4 Pins			1 Cable
Mainboard 12v	Onboard	45cm 4+4 Pins			1 Cable
Graphics	Onboard	45cm 6+2 Pins	+15cm 6 Pins		1 Cable
Peripherals	Onboard	45cm SATA 15 Pins	+15cm SATA 15 Pins	+15cm SATA 15 Pins	2 Cables
Peripherals	Onboard	45cm Molex 4Pins	+15cm Molex 4 Pins		1 Cable
Peripherals	Onboard	45cm Molex 4Pins	+15cm Molex 4 Pins	+15cm FDD 4Pins	1 Cable

### Technical Specifications:

Recom RC-ProE-A600								
MODEL	Recom RC-ProE-A600							
AC INPUT	230VAC, 7A, 50-60hz							
DC OUTPUT	+3.3V	+5V	+12V1	+12V2	+12V3	+12V4	-12V	+5VSB
Max Amps	24A	24A	22A	22A	n/a	n/a	0,5A	2A
Max Combined	150W		482W				6W	10W
Total Combined	584W						16W	
Total power	600W							

