

# Product Data Comparison Sheet Recom PSU

[www.recom.nl](http://www.recom.nl)

	M/B 20+4Pins	M/B 8 Pins ATX EPS 12V	M/B 4 Pins ATX EPS 12V	M/B 4+4 Pins ATX EPS 12V	Pci-E 8 Pins	Pci-E 6+2 Pins	Pci-E 6 Pins	Sata 15 Pins	HDD 4 Pins	FDD 4 Pins	Power Input (Volts)	Fan Size (Cm)	PFC	OVP	OPP	SCP	12 Volt line 1 max Ampere	12 Volt line 2 max Ampere	12 Volt line 3 max Ampere	12 Volt line 4 max Ampere	3,3 Volt line max Ampere	5 Volt line max Ampere	Total Power Watts	ATX 12v version	Modulair cabling	80 Plus	80Plus Bronze	0dB Design
RC-PE450Plus	1		1			1	3	3	1	230	12	Yes	Yes	Yes	Yes	20	20			25	25	450	2.0					
RC-PE550Plus	1			1	1		4	4	1	230	14	Yes	Yes	Yes	Yes	22	22			25	25	550	2.0					
RC-PEM500	1			1	1		4	4	1	230	14	Yes	Yes	Yes	Yes	20	20			25	25	500	2.0	Yes				
RC-PEM600	1			1	1	1	6	4	1	230	14	Yes	Yes	Yes	Yes	22	22			25	25	600	2.2	Yes				
RC-PE0DB580	1			1	1	1	6	5	1	90-264	12	Yes	Yes	Yes	Yes	20	20			25	25	580	2.2		Yes		Yes	
RC-ProE-A500	1			1	1	1	6	4	1	230	12	Yes	Yes	Yes	Yes	20	20			24	24	500	2.3		Yes	Yes		
RC-ProE-A600	1			1	1	1	6	4	1	230	12	Yes	Yes	Yes	Yes	22	22			24	24	600	2.3		Yes	Yes		
RC-ProE-M850	1	1	1			2	2	8	8	2	115-230	14	Yes	Yes	Yes	Yes	34	34	34	34	24	30	850	2.3	Yes	Yes	Yes	
RC-ProE-M1050	1	1	1			3	3	8	8	2	115-230	14	Yes	Yes	Yes	Yes	38	38	38	38	24	30	1050	2.3	Yes	Yes	Yes	

	RC-PE450Plus	RC-PE550Plus	RC-PEM500	RC-PEM600	RC-PE0DB580	RC-ProE-A500	RC-ProE-A600	RC-ProE-M850	RC-ProE-M1050
High Efficient					X	X	X	X	X
Complete Silent (0Db)					X				
Extreme Gaming							X	X	
Modulair			X	X			X	X	

	RC-PE450Plus	RC-PE550Plus	RC-PEM500	RC-PEM600	RC-PE0DB580	RC-ProE-A500	RC-ProE-A600	RC-ProE-M850	RC-ProE-M1050
Mediacenter					X	X	X		
Price wise	X	X	X	X					
Cost efficient					X	X	X	X	
Desktop system	X	X	X	X	X				

