

RC-PE450PlusII 450Watts




Keypoints:

- Cable length at least 50 cm
- Includes 6+2Pins Pci-E Connector
- Conform Intel ATX 12v ver 2.0 and EPS 12v
- PFC (Power factor correction)
- Silent 12cm fan (automatic speed control)
- OCP / OVP / SCP Protections
- Optimized silent design with minimal noise

Specifications:

Description	
Article number	RC-PE450PlusII
Packaging unit (per carton)	6 Pieces
Net weight per piece	1,627 Kg
Gross weight per piece	1,983 Kg
Gross weight per carton	12,6 Kg
Net dimensions per piece (W x H x D)	14 x 15 x 8,6cm
Gross dimensions per piece (W x H x D)	17,5 x 9,5 x 26cm
Gross dimensions per carton (W x H x D)	30,5 x 20 x 53,5 cm
Color	Black coated shell
On-Off power switch	Yes
Accessories	2 Pcs. Cable ties 4 Pcs. Black screws AC Powercable (CE)



Connectors:

Description	
M/B 20+4Pins	1 Pc.
M/B 4 Pins ATX	1 Pc.
Pci-E 6+2 Pins	1 Pc.
SATA 15 Pins	3 Pcs.
MOLEX 4 Pins	3 Pcs.
FDD 4 Pins	1 Pc.

Delivered cables:

	Connector 1	Connector 2	Connector 3	Connector 4
Mainboard atx	50cm 20+4 Pins			
Mainboard 12v	50cm 4 Pins			
Graphics	40cm 6+2 Pins			
Peripherals	40cm SATA 15 Pins	+15cm SATA 15 Pins	+15cm Molex 4 Pins	
Peripherals	40cm SATA 15 Pins	+15cm Molex 4 Pins	+15cm Molex 4 Pins	+15cm FDD 4 Pins

Technical Specifications:

MODEL								
Recom RC-PE450PlusII								
AC INPUT								
230VAC, 6A, 50hz								
DC OUTPUT	+3.3V	+5V	+12V1	+12V2	+12V3	+12V4	-12V	+5VSB
Max Amps	25A	25A	20A	20A	n/a	n/a	0,5A	2,0A
Max Combined	160W		360W				6W	10W
Total Combined	434W						16W	
Total power	450W							

