

RC-PE600Plus 600Watts



Keypoints:

- ErP/EuP ready (Standby <1 watt EU norm)
- Conform Intel ATX 12v ver 2.0 and EPS 12v
- Active PFC (Power factor correction)
- Cable length at least 50 cm
- Supports SLI & Crossfire (2x 6+2Pins Pci-E)
- Efficiency > 80%
- Silent 12cm fan (automatic speed control)
- OCP / OVP / SCP Protections

Specifications:

Description	
Article number	RC-PE600Plus
Packaging unit (per carton)	6 Pieces
Net weight per piece	1,444 Kg
Gross weight per piece	1,798 kg
Gross weight per carton	11,4 Kg
Net dimensions per piece (W x H x D)	14 x 15 x 8,6cm
Gross dimensions per piece (W x H x D)	17,5 x 9,5 x 26cm
Gross dimensions per carton (W x H x D)	30,5 x 20 x 53,5 cm
Color	Black coated shell
On-Off power switch	Yes
Accessories	2 Pcs. Cable ties 4 Pcs. Black screws AC Powercable (CE)



Connectors:

Description	
M/B 20+4Pins	1 Pc.
M/B 4+4 Pins ATX	1 Pc.
Pci-E 6+2 Pins	2 Pcs.
SATA 15 Pins	6 Pcs.
MOLEX 4 Pins	5 Pcs.
FDD 4 Pins	1 Pc.

Delivered cables:

	Connection	Connector 1	Connector 2	Connector 3	Amount
Mainboard atx	Onboard	50cm 20+4 Pins			1 Cable
Mainboard 12v	Onboard	50cm 4+4 Pins			1 Cable
Graphics	Onboard	40cm 6+2 Pins	+15cm 6+2 Pins		1 Cable
Peripherals	Onboard	40cm SATA 15 Pins	+15cm SATA 15 Pins	+15cm Molex 4 Pins	3 Cables
Peripherals	Onboard	40cm Molex 4Pins	+15cm Molex 4 Pins	+15cm FDD 4 Pins	1 Cable

Technical Specifications:

Recom RC-PE600Plus									
MODEL	Recom RC-PE600Plus								
AC INPUT	230VAC, 6A, 50hz								
DC OUTPUT	+3.3V	+5V	+12V1	+12V2	+12V3	+12V4	-12V	+5VSB	
Max Amps	24A	24A	22A	22A	n/a	n/a	0,5A	2,5A	
Max Combined	150W		432W				6W	12,5W	
Total Combined	581,5W						18,5W		
Total power	600W								

