


Keypoints:

- 80+ 85% efficient
- Conform Intel ATX 12v ver 2.2 and EPS 12v
- **One Single +12V Rail (max. 50A/600W)**
- Active PFC (Power factor correction)
- Cable length at least 50 cm (sleeved)
- Silent 14cm fan (automatic speed control)
- Patented angled fan frame
- **Two forward switching design**



Specifications:

Description	
Article number	RC-PE750Plus
Packaging unit (per carton)	6 Pieces
Net weight per piece	1,937 Kg
Gross weight per piece	2,342 kg
Gross weight per carton	14,12 Kg
Net dimensions per piece (W x H x D)	15,5 x 15 x 8,6cm
Gross dimensions per piece (W x H x D)	20,5 x 11 x 27cm
Gross dimensions per carton (W x H x D)	30,5 x 20 x 53,5 cm
Color	Black coated shell
On-Off power switch	Yes
Accessories	3 Pcs. Cable ties 4 Pcs. Black screws AC Powercable (CE)



Delivered cables:

	Connection	Connector 1	Connector 2	Connector 3	Amount
Mainboard atx	Onboard	50cm 20+4 Pins			1 Cable
Mainboard 12v	Onboard	50cm 4+4 Pins			1 Cable
Graphics	Onboard	40cm 6+2 Pins	+15cm 6+2 Pins		1 Cable
Peripherals	Onboard	40cm SATA 15 Pins	+15cm SATA 15 Pins	+15cm Molex 4 Pins	3 Cables
Peripherals	Onboard	40cm Molex 4Pins	+15cm Molex 4 Pins	+15cm FDD 4 Pins	1 Cable

Technical Specifications:

Recom RC-PE750Plus					
MODEL	Recom RC-PE750Plus				
AC INPUT	200~240VAC, 6A, 50hz				
DC OUTPUT	+3.3V	+5V	+12V1	-12V	+5VSB
Max Amps	24A	24A	50A	0,5A	2,5A
Max Combined	150W		600W	6W	12,5W
Total power	750W				

Connectors:

Description	
M/B 20+4Pins	1 Pc.
M/B 4+4 Pins ATX	1 Pc.
Pci-E 6+2 Pins	2 Pcs.
SATA 15 Pins	6 Pcs.
MOLEX 4 Pins	5 Pcs.
FDD 4 Pins	1 Pc.

• PSU supports OCP / OVP / SCP Protections

